

# (12) UK Patent Application (19) GB (11) 2 368 154 (13) A

(43) Date of A Publication 24.04.2002

(21) Application No 0107964.9

(22) Date of Filing 29.03.2001

(30) Priority Data

(31) 09543952

(32) 06.04.2000

(33) US

(71) Applicant(s)

International Business Machines Corporation  
(Incorporated in USA - New York)  
Armonk, New York 10504, United States of America

(72) Inventor(s)

Brad B Topol  
Arthur R Francis

(74) Agent and/or Address for Service

P Waldner  
IBM United Kingdom Limited, Intellectual Property  
Department, Hursley Park, WINCHESTER, Hampshire,  
SO21 2JN, United Kingdom

(51) INT CL<sup>7</sup>

G06F 17/30

(52) UK CL (Edition T )

G4A AUDB

(56) Documents Cited

WO 99/61983 A

WO 01/16700 A

WO 01/11905 A

US 6253326 A

(58) Field of Search

UK CL (Edition T ) G4A AUDB

INT CL<sup>7</sup> G06F 17/30

Online: WPI, EPODOC, JAPIO & Internet

(54) Abstract Title

**Systems, apparatus and method for transformation of Java server pages to PvC format**

(57) A system, apparatus and method for transforming Java Server Pages (JSPs) into pervasive computing (PvC) device specific JSPs. An original JSP is parsed for JSP tags. The JSP tags are converted to HyperText Mark-up Language (HTML) comment tags. The JSP is then transformed into a PvC device specific JSP by converting the HTML tags in the JSP to HTML tags for a specific PvC device. The HTML comment tags are then parsed for the comment tags having embedded JSP tags. The JSP tags are then restored by removing the HTML comment tag identifiers. A PvC device specific JSP is thus created.




FIG. 5

GB 2 368 154 A






FIG. 1

**FIG. 2**

```

<HTML>
<HEAD>
<TITLE>Welcome to the Halloween House of Terror</TITLE>
<BODY>
<H1>Welcome to the Halloween House of Terror!!</H1>
<HR>
<P>Voted the most frightening haunted house three years in a row, the <STRONG>Halloween
House of Terror</STRONG> provides the ultimate in Halloween thrills. Over <STRONG>20 rooms
of thrills and Excitement</STRONG> to make your blood run cold and your hair stand on end!</P>
<P>The Halloween House of Terror is open from <EM>October 20 to November 1st</EM>, with a
gala celebration on Halloween night. Our hours are:</P>
<UL>
<LI>Mon-Fri 5pm-midnight
<LI>Sat & Sun 5pm-3AM
<LI><STRONG>Halloween Night (10/31)</STRONG>: 3pm-???
</UL>
<P>The Halloween House of Terror is located at:<BR>
The Old Waterfall Shopping Center<BR>
1020 Mirabella Ave<BR>
Springfield, CA 94532<BR>
</P>
</BODY>
</HTML>

```



Welcome to the Halloween House of Terror

---

## Welcome to the Halloween House of Terror !!

---

Voted the most frightening haunted house three years in a row, the **Halloween House of Terror** provides the ultimate in Halloween thrills. Over **20 rooms of thrills and Excitement** to make your blood run cold and your hair stand on end!

The Halloween House of Terror is open from October 20 to November 1st, with a gala celebration on Halloween night. Our hours are:

Mon-Fri 5pm-midnight  
 Sat & Sun 5pm-3AM  
**Halloween Night (10/31): 3pm-???**

The Halloween House of Terror is located at:  
 The Old Waterfall Shopping Center  
 1020 Mirabella Ave  
 Springfield, CA 94532


FIG. 3


```


410 { <HTML>
    <HEAD>
    <TITLE>Welcome to the Halloween House of Terror</TITLE>
    <BODY>
    <H1>Welcome to the Halloween House of Terror!!</H1>
    <HR>
    <P>Voted the most frightening haunted house three years in a row, the <STRONG>Halloween
    House of Terror</STRONG> provides the ultimate in Halloween thrills. Over <STRONG>20 rooms
    of thrills and Excitement</STRONG> to make your blood run cold and your hair stand on end!</P>
    <P>The Halloween House of Terror is open from <EM>October 20 to November 1st</EM>, with a
    gala celebration on Halloween night.</P>
440 { <jsp:forward page="{www.hauntedhouse.com!<%=HauntedHouse.class%}" />
    <P>Our hours are:</P>
    <UL>
    <LI>Mon-Fri 5pm-midnight
    <LI>Sat & Sun 5pm-3AM
    <LI><STRONG>Halloween Night (10/31)</STRONG>: 3pm-???
    </UL>
    <P>The Halloween House of Terror is located at:<BR>
    The Old Waterfall Shopping Center<BR>
    1020 Mirabella Ave<BR>
    Springfield, CA,94532<BR>
    </P>
    </BODY>
    </HTML>
    }
430

```

FIG. 4

**FIG. 5**

**FIG. 6**



**FIG. 7**

SYSTEM, APPARATUS AND METHOD FOR TRANSFORMATION  
OF JAVA SERVER PAGES INTO PVC FORMATS

BACKGROUND OF THE INVENTION

5 The present invention is directed to a system, apparatus and method for the transformation of Java server pages into formats for various pervasive computing (PvC) devices.

10 The use of Java Server Pages (JSPs) for the generation of dynamic HyperText Mark-up Language (HTML) content is becoming more popular. JSP provides a methodology by which information related to the content and information related to the presentation of the content may be separated. For example, JSP provides a <bean> tag which is utilized to obtain content,  
15 such as Java applets, while HTML tags are used to specify presentation of the content.

A problem arises in these prior JSPs in that they are designed with the assumption that the presentation of the content will be rendered in a  
20 browser that executes on a desktop workstation with a full-sized, high resolution, full-color monitor. As the use of mobile handheld pervasive computing (PvC) devices becomes more prevalent, the assumption used in the design of JSPs becomes a stumbling block since there is a need to deliver the JSP to a variety of PvC devices whose browsing screen size capabilities  
25 are drastically different from that of a desktop workstation.

One way to address this problem is to have a transcoding proxy server, or servlet, intercept the JSP and transcode it dynamically, i.e.,  
30 on the fly, as the JSP is being sent to the PvC device. This option results in extra overhead costs incurred each and every time the JSP is invoked.

A second approach to solving this problem is to have a human JSP  
35 developer design and create separate JSPs for each and every PvC device one might want to support. This approach has the disadvantage of extra cost required to have the additional JSPs authored by a human developer who needs to be cognizant of the capabilities of the PvC devices he or she intends to support.

40 Thus, it would be advantageous to have a system, apparatus and method that provides a mechanism by which JSPs may be automatically converted to formats useable by a plurality of PvC devices.

### SUMMARY OF THE INVENTION

One aspect of the present invention provides A method of transforming an original Java Server Page (JSP) file into a pervasive computing (PvC) device specific JSP file, comprising: parsing the original JSP file for JSP tags; masking the JSP tags; converting non-masked tags in the original JSP file into PvC device specific format tags; unmasking the JSP tags; and storing a transformed JSP file containing the PvC device specific format tags and the JSP tags.

A second aspect of the present invention provides an apparatus for transforming an original Java Server Page (JSP) file into a pervasive computing (PvC) device specific JSP file, comprising: a processor; and a storage device, wherein the processor parses the original JSP file stored on the storage device for JSP tags, masks the JSP tags, converts non-masked tags in the original JSP file into PvC device specific format tags, unmask the JSP tags, and stores a transformed JSP file containing the PvC device specific format tags and the JSP tags on the storage device.

A third aspect of the present invention provides a computer program product in a computer readable medium for transforming an original Java Server Page (JSP) file into a pervasive computing (PvC) device specific JSP file, comprising: first instructions for parsing the original JSP file for JSP tags; second instructions for masking the JSP tags; third instructions for converting non-masked tags in the original JSP file into PvC device specific format tags; fourth instructions for unmasking the JSP tags; and fifth instructions for storing a transformed JSP file containing the PvC device specific format tags and the JSP tags.

### BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

**Figure 1** is an exemplary block diagram of a distributed data processing system according to the present invention;

**Figure 2** is an exemplary block diagram of a server according to the present invention;

Figure 3 is an exemplary diagram illustrating the use of HTML tags to create an HTML document;

Figure 4 is an exemplary diagram of the use of JSP tags along with HTML tags in a JSP;

Figure 5 is an exemplary diagram illustrating the phases of operation of the present invention;

Figure 6 is a flowchart outlining an exemplary operation of the present invention; and

Figure 7 is a flowchart outlining an exemplary operation of the present invention for converting a JSP file to a Pvc specific JSP file.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, and in particular with reference to Figure 1, a pictorial representation of a distributed data processing system is depicted in which the present invention may be implemented. Distributed data processing system 100 is a network of computers in which the present invention may be implemented. Distributed data processing system 100 contains network 102, which is the medium used to provide communications links between various devices and computers connected within distributed data processing system 100. Network 102 may include permanent connections, such as wire or fiber optic cables, or temporary connections made through telephone connections. Network 102 may further include wireless communication connections through, for example, base stations, satellites, and the like, for communicating with wireless communication devices.

In the depicted example, server 104 is connected to network 102, along with storage unit 106. In addition, clients 108, 110, 112 and 118 are also connected to network 102. These clients, 108, 110, 112 and 118, may be, for example, personal computers, network computers, personal digital assistants (PDAs), alphanumeric pagers, cellular telephones, and the like. Any communication device, either wired or wireless, that is capable of receiving and displaying a Java Server Page (JSP) is intended to be within the scope of the term "client" as used in this disclosure.

In the depicted example, server 104 provides data, such as boot files, operating system images and applications, and in particular JSPs, to clients 108-118. Clients 108-118 are clients to server 104. Distributed

data processing system 100 may include additional servers, clients, and other devices not shown.

5 In the depicted example, distributed data processing system 100 is the Internet, with network 102 representing a worldwide collection of networks and gateways that use the TCP/IP suite of protocols to communicate with one another. At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers consisting of thousands of commercial, government, education, and other computer  
10 systems that route data and messages. Of course, distributed data processing system 100 also may be implemented as a number of different types of networks such as, for example, an intranet or a local area network. Figure 1 is intended as an example and not as an architectural limitation for the processes of the present invention.

15 Referring to Figure 2, a block diagram of a data processing system which may be implemented as a server, such as server 104 in Figure 1, is depicted in accordance with the present invention. Data processing system 200 may be a symmetric multiprocessor (SMP) system including a plurality of  
20 processors 202 and 204 connected to system bus 206. Alternatively, a single processor system may be employed. Also connected to system bus 206 is memory controller/cache 208, which provides an interface to local memory 209. I/O bus bridge 210 is connected to system bus 206 and provides an interface to I/O bus 212. Memory controller/cache 208 and I/O bus bridge  
25 210 may be integrated as depicted. Peripheral component interconnect (PCI) bus bridge 214 connected to I/O bus 212 provides an interface to PCI local bus 216. A number of modems 218-220 may be connected to PCI bus 216. Typical PCI bus implementations will support four PCI expansion slots or add-in connectors.

30 Communications links to network computers 108-112 in Figure 1 may be provided through modem 218 and network adapter 220 connected to PCI local bus 216 through add-in boards. Additional PCI bus bridges 222 and 224 provide interfaces for additional PCI buses 226 and 228, from which  
35 additional modems or network adapters may be supported. In this manner, server 200 allows connections to multiple network computers. A memory mapped graphics adapter 230 and hard disk 232 may also be connected to I/O bus 212 as depicted, either directly or indirectly.

40 Those of ordinary skill in the art will appreciate that the hardware depicted in Figure 2 may vary. For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in place of the hardware depicted. The depicted example is not meant to imply

architectural limitations with respect to the present invention. The data processing system depicted in **Figure 2** may be, for example, an IBM RISC/System 6000, a product of International Business Machines Corporation in Armonk, New York, running the Advanced Interactive Executive (AIX) operating system.

The server 200 stores a Java Server Page (JSP) that is designed for presentation on a typical desktop workstation, such as client device 108. The JSP is comprised of, for example, text, images and tags that are used to generate a JSP presentation on a client device when the JSP is downloaded to the client device. For example, the JSP may comprise text, HyperText Mark-up Language (HTML) tags identifying presentation formats of the text, HTML tags identifying in-line image files to be displayed, and JSP tags. JSP tags are used to encapsulate scripting language fragments into an HTML page. JSP pages use JSP tags or scriptlets to generate the dynamic content on the page (the content that changes according to the request, such as requested account information or the price of a specific bottle of wine). The logic that generates the content is encapsulated in tags and JavaBean components, and tied together in scriptlets, all of which are executed on the server side. More information regarding JSP technology and JSP tags may be obtained from the JSP section of the Sun Corporation Web site at <http://java.sun.com/products/jsp>, which is hereby incorporated by reference.

While the present invention will be described with reference to HTML tags, one of ordinary skill in the art should appreciate that any mark-up language, such as XML, may be utilized without departing from the spirit and scope of the present invention.

**Figure 3** illustrates an example of the use of HTML tags to dictate the manner in which text information is displayed by a browser on a client device. As shown in **Figure 3**, the HTML tags may include tags identifying headers, titles, text bodies, paragraphs, underlining, bold text, and the like. The bottom portion of **Figure 3** shows how these tags are processed by the browser application to generate a formatted Web page for display to a user.

JSPs use tags in a similar manner as the HTML tags shown in **Figure 3** to designate the format of the JSP page as it will be displayed. The JSPs further include JSP tags designating JSP components, such as Java beans or applets, that are to be executed when accessing the JSP. **Figure 4** provides an example of the use of HTML tags and JSP tags for a simplified JSP. As shown in **Figure 4**, the JSP includes HTML tags 410 and 420 that designate formatting of text information 430. The JSP further includes JSP

tag 440, which reads "<jsp:forward  
page="{www.hauntedhouse.com|<%=HauntedHouse.class%}">/>", that forwards a  
client request to a JSP file "HauntedHouse.class" for processing.

5           The JSP tags are applicable to any client device.       Thus, the JSP  
tags need not be modified when converting a general JSP to a PvC device  
specific JSP for a PvC device having different capabilities than a desktop  
workstation. The HTML tags, however, do require modification so that they  
are consistent with the capabilities of the PvC device to which the JSP is  
10       transmitted.

          The present invention provides a system, apparatus and method for  
converting JSPs designed for desktop workstations, into JSPs that are  
useable by a plurality of PvC devices. The present invention parses a JSP  
15       to locate and mask the JSP tags and convert the HTML tags to PvC device  
specific HTML tags. The method according to the present invention may be  
implemented, for example, as one or more Java applications, applets, or  
Java beans resident on a server of a distributed data processing system,  
such as server 140 or server 200.

20           The Java beans may be executed when, for example, a system operator  
designates, via an input device (not shown), that a JSP is to be converted  
for use by PvC devices. Alternatively, the Java beans may be executed when  
a request is first received from a PvC device.

25           For example, with reference to **Figures 1 and 2**, when a request for a  
JSP is received by a server 200 from a PvC device, such as PvC device 110,  
the server 200 receives the request via the network adapter 220. The  
server 200 then processes request by parsing header information of the  
30       request to determine the type of PvC device from which the request was  
received. For example, the header of the request may include a device type  
identifier indicating the type of device that sent the request.

          The server 200 may then search for a stored version of the requested  
35       JSP on hard disk 232 corresponding to the PvC device from which the request  
was received. This search may be based on, for example, filename and  
filename extension. The various PvC device specific JSPs may be stored  
under the same filename with different extensions designating the PvC for  
which the JSP is formatted. Alternatively, the filenames may be different  
40       based on the PvC for which they are formatted.

          If an appropriate version is available, the JSP is sent to the PvC  
device. However, if an appropriate version is not available, the server  
200 may invoke the Java beans to convert the JSP into a PvC specific JSP

for the particular PvC device sending the request. This PvC specific JSP will then be stored on the server and utilized when later requests from similar PvC devices are received.

5           **Figure 5** is an illustration of the various phases implemented by the present invention. As shown in **Figure 5**, phase I of operating involves parsing the original JSP file 510 to produce a resultant file 520. Through parsing of the original JSP file 510, the HTML tags and JSP tags in the JSP are identified. The HTML tags and JSP tags are identified by looking for  
10           the occurrence of symbols designating the various tags. As the JSP file 510 is parsed, HTML constructs and HTML tags are written to a resultant file 520. JSP tags are masked by writing them to the resultant file 520 as HTML comment tags. Thus, the resultant file 520 contains only valid HTML constructs, i.e., HTML tags and textual information. HTML tags are  
15           indicators in HTML documents that identify document elements, structure, formatting, and hypertext links to other documents or to included media. Enclosed within these tags is textual information that is presented to the display device.

20           Next, in phase II of the operation, the resultant file 520 is transcoded into one or more PvC device specific files 530. The JSP tags that are embedded as HTML comment tags remain in the transcoded files 530 as HTML comment tags. The transcoding of the resultant file 520 into PvC specific files 530 involves placing the identified HTML tags into a  
25           document object model and performing a transcoding node by node. As is known to those of ordinary skill in the art, a document object model provides a representation of the hierarchical arrangement of document tags in a tree-like structure. Each node of the document object model represents a document tag.

30           The transcoding of the present invention proceeds through the document object model node by node and converts the HTML tag associated with the node to a corresponding tag in a mark-up language useable by the particular PvC device. For example, the HTML tag may be converted to an  
35           equivalent Wireless Mark-up Language (WML) tag or a Handheld Device Markup Language (HDML) tag. Any tags that aren't supported by the mark-up language for the PvC device are removed and replaced with a closest equivalent.

40           As a part of this processing phase, the occurrence of in-line images will also be transcoded to the resolution of the target device. As a result of the image transcoding process, static representation of the original image will be saved with a new file extension that indicates the

image conversion format. In conjunction with the image transcoding process, the links to the images in each of the generated files will be updated to reflect the transcoded file that contains the resolution requirements of the target PvC device.

In the third phase of the operation, the JSP tags are unmasked. This phase involves parsing the transcoded files, locating the hidden JSP tags and converting the file back to a valid JSP file. This may be done by parsing the transcoded files, identifying HTML comment tags, determining if the content of the HTML comment tags fit the format of a JSP tag, and removing the HTML comment tag identifiers when saving the transcoded file to thereby restore the JSP tags. In this way, a JSP file is generated that is transcoded for a specific PvC device.

**Figure 6** is a flowchart outlining an exemplary operation of the present invention. As shown in **Figure 6**, the operation starts with receiving a request for a JSP from a PvC device (step 601). A search is then conducted for a version of the JSP that is useable by the requesting PvC device (step 602). A determination is made as to whether or not a JSP for the requesting PvC device is found (step 603). If so, the JSP is sent to the PvC device (step 604). If not, a JSP for the requesting PvC device is generated and stored (step 605). The generated JSP is then sent to the requesting PvC device (step 606). The operation then ends.

While step 605 above is described as generating only the PvC specific JSP for the requesting PvC device, the operation is not limited to such. Rather, the PvC specific JSPs for all supported PvC devices may be generated. Additionally, the PvC specific JSPs may be generated in response to a command received from a user, such as a system operator.

**Figure 7** is a flowchart outlining an exemplary operation of the present invention when generating a PvC specific JSP from an original JSP. This operation may be implemented as step 605 in **Figure 6**, described above.

As shown in **Figure 7**, the operation starts with reading a JSP file and storing the contents of the JSP file in a buffer memory (step 701). The contents of the JSP file are then parsed (step 702). A determination is made as to whether or not a tag is encountered (step 703). If not, the contents are written to a resultant file (step 704). If so, a determination is made as to whether the tag is an HTML tag (step 705). If so, the HTML tag is written to the resultant file (step 706).

If not, the tag must be a JSP tag. The JSP tag is then converted to an HTML comment tag and written to the resultant file (step 707). The process is then repeated until an end of file is encountered (step 708).

5           Thereafter, it is determined for which PvC devices the JSP will be converted (step 709). Then, for each PvC device, the following steps are performed. The HTML tags in the resultant file are transcoded to PvC device specific tags (step 710). A transcoded file is then stored for the  
10           PvC device containing the transcoded HTML tags and resultant file content (step 711). A determination is then made as to whether there are more PvC devices for which the JSP should be transcoded (step 712). If so, the operation returns to step 710. If not, the operation proceeds to phase III.

15           In phase III, the operation performs the following steps for each of the PvC specific transcoded files that were created. The transcoded file is parsed for HTML comments tags (step 713). A determination is made as to whether a tag is encountered (step 714). If not, the operation continues to parse the transcoded file until an end of file is encountered (step 718)  
20           at which time the operation ends.

          If a tag is encountered, it is determined whether or not the tag is an HTML comment tag (step 715). If not, the operation continues to parse the transcoded file until an end of file is encountered (step 718) at which  
25           time the operation ends. If so, a determination is made as to whether the HTML comment tag contains a JSP tag (step 716). If not, the operation goes to step 718. If so, the operation removes the HTML comment tag identifiers (step 717) and continues to parse the transcoded file until an end of file is encountered (step 718). The transcoded file with the restored JSP tags  
30           is then stored (step 719). After all of the transcoded files are processed, the operation ends.

          Thus, the present invention provides a system, apparatus and method for automatically generating PvC specific JSP files from a general JSP  
35           file. In this way, the expense of providing JSP files for a variety of PvC devices is greatly reduced.

          It is important to note that while the present invention has been described in the context of a fully functioning data processing system,  
40           those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of

signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media such a floppy disc, a hard disk drive, a RAM, CD-ROMs, and transmission-type media such as digital and analog communications links.

In summary there is described a system, apparatus and method for transforming Java Server Pages (JSPs) into pervasive computing (PvC) device specific JSPs. An original JSP is parsed for JSP tags. The JSP tags are converted to HyperText Mark-up Language (HTML) comment tags. The JSP is then transformed into a PvC device specific JSP by converting the HTML tags in the JSP to HTML tags for a specific PvC device. The HTML comment tags are then parsed for the comment tags having embedded JSP tags. The JSP tags are then restored by removing the HTML comment tag identifiers. A PvC device specific JSP is thus created.

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

## CLAIMS:

1. A method of transforming an original Java Server Page (JSP) file into a pervasive computing (PvC) device specific JSP file, comprising:

parsing the original JSP file for JSP tags;

masking the JSP tags;

converting non-masked tags in the original JSP file into PvC device specific format tags;

unmasking the JSP tags; and

storing a transformed JSP file containing the PvC device specific format tags and the JSP tags.

2. The method of claim 1, wherein masking the JSP tags includes embedding the JSP tags into HyperText Mark-up Language (HTML) comment tags.

3. The method of claim 2, wherein unmasking the JSP tags includes removing HTML comment tag identifiers from the HTML comment tags in which the JSP tags are embedded.

4. The method of claim 1, 2 or 3 wherein storing the transformed JSP file includes storing the transformed JSP file with a filename that is unique to the particular PvC device for which the JSP file is formatted.

5. The method of claim 4, wherein the filename has a unique extension for the PvC device for which the JSP file is formatted.

6. The method of any one of claims 1 to 5, wherein parsing the original JSP file comprises:

determining if a tag is encountered;

if a tag is encountered, determining if the tag is an HTML tag; and

if the tag is not an HTML tag, identifying the tag as a JSP tag.

7. The method of claim 6, wherein parsing the original JSP file further comprises:

if a tag is not encountered, writing the JSP file content to a resultant file;

5       if the tag is a HTML tag, writing the HTML tag to the resultant file;  
and

if the tag is a JSP tag, writing the JSP tag to the HTML file embedded in an HTML comment tag.

10       8.     An apparatus for transforming an original Java Server Page (JSP) file into a pervasive computing (PvC) device specific JSP file, comprising:

a processor; and

15       a storage device, wherein the processor parses the original JSP file stored on the storage device for JSP tags, masks the JSP tags, converts non-masked tags in the original JSP file into PvC device specific format tags, unmaskes the JSP tags, and stores a transformed JSP file containing the PvC device specific format tags and the JSP tags on the  
20       storage device.

9.     The apparatus of claim 8, wherein the processor masks the JSP tags by embedding the JSP tags into HyperText Mark-up Language (HTML) comment tags.

25       10.    The apparatus of claim 9, wherein the processor unmaskes the JSP tags by removing HTML comment tag identifiers from the HTML comment tags in which the JSP tags are embedded.

30       11.    The apparatus of claim 8 or 9, wherein the processor stores the transformed JSP file with a filename that is unique to the particular PvC device for which the JSP file is formatted.

35       12.    The apparatus of claim 11, wherein the filename has a unique extension for the PvC device for which the JSP file is formatted.

13.    The apparatus of claim 8, 9, 10 or 11 wherein while the processor parses the JSP file the processor:

determines if a tag is encountered;

40

if a tag is encountered, determines if the tag is an HTML tag; and

if the tag is not an HTML tag, identifies the tag as a JSP tag.

14. The apparatus of any one of claims 8 to 13, wherein while the processor parses the JSP file, the processor further:

writes the JSP file content to a resultant file, if a tag is not encountered;

writes the HTML tag to the resultant file, if the tag is a HTML tag; and

writes the JSP tag to the HTML file embedded in an HTML comment tag, if the tag is a JSP tag.

15. A computer program product in a computer readable medium for transforming an original Java Server Page (JSP) file into a pervasive computing (PvC) device specific JSP file, comprising:

first instructions for parsing the original JSP file for JSP tags;

second instructions for masking the JSP tags;

third instructions for converting non-masked tags in the original JSP file into PvC device specific format tags;

fourth instructions for unmasking the JSP tags; and

fifth instructions for storing a transformed JSP file containing the PvC device specific format tags and the JSP tags.

16. The computer program product of claim 15, wherein the second instructions include instructions for embedding the JSP tags into HyperText Mark-up Language (HTML) comment tags.

17. The computer program product of claim 16, wherein the fourth instructions include instructions for removing HTML comment tag identifiers from the HTML comment tags in which the JSP tags are embedded.

18. The computer program product of claim 15 or 16, wherein the fifth instructions include instructions for storing the transformed JSP file with a filename that is unique to the particular PvC device for which the JSP file is formatted.

19. The computer program product of claim 18, wherein the filename has a unique extension for the PvC device for which the JSP file is formatted.

20. The computer program product of any one of claims 15 to 19, wherein the first instructions include instructions for:

determining if a tag is encountered;

if a tag is encountered, determining if the tag is an HTML tag; and

if the tag is not an HTML tag, identifying the tag as a JSP tag.

21. The computer program product of claim 20, wherein the first instructions further include instructions for:

writing the JSP file content to a resultant file, if a tag is not encountered;

writing the HTML tag to the resultant file, if the tag is an HTML tag; and

writing the JSP tag to the HTML file embedded in an HTML comment tag, if the tag is a JSP tag.

22. A system for transforming an original Java Server Page (JSP) file into a pervasive computing (PvC) device specific JSP file, comprising:

means for parsing the original JSP file for JSP tags;

means for masking the JSP tags;

means for converting non-masked tags in the original JSP file into PvC device specific format tags;

means for unmasking the JSP tags; and

means for storing a transformed JSP file containing the PvC device specific format tags and the JSP tags.

23. The system of claim 22, wherein the means for masking embeds the JSP tags into HyperText Mark-up Language (HTML) comment tags.

24. The system of claim 23, wherein the means for unmasking removes HTML comment tag identifiers from the HTML comment tags in which the JSP tags are embedded.

25. The system of claim 22, wherein the means for storing stores the transformed JSP file with a filename that is unique to the particular PvC device for which the JSP file is formatted.

5 26. The system of claim 25, wherein the filename has a unique extension for the PvC device for which the JSP file is formatted.

10 27. The system of any one of claims 22 to 26, wherein the means for parsing determines if a tag is encountered, determines if the tag is an HTML tag, if a tag is encountered, and if the tag is not an HTML tag, identifies the tag as a JSP tag.

15 28. The system of claim 27, wherein the means for parsing further writes the JSP file content to a resultant file, if a tag is not encountered, writes the HTML tag to the resultant file, if the tag is an HTML tag, and writes the JSP tag to the HTML file embedded in an HTML comment tag, if the tag is a JSP tag.



INVESTOR IN PEOPLE

Application No: GB 0107964.9  
Claims searched: 1 to 28

16  
Examiner: Jason Clee  
Date of search: 13 February 2002

## Patents Act 1977 Search Report under Section 17

### Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.T): G4A(U): AUSB

Int Cl (Ed.7): G06F: 17/30

Other: Online: WPI, EPODOC, JAPIO & Internet

### Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
A	WO 01/16700 A (TAO Group Plc)	-
A	WO 01/11905 A (Ericsson Inc)	-
A	WO 99/61983 A (Telefonaktiebolaget Ericsson L M)	-
A	US 6253326 (Palm Inc.)	-

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.